

BRAKE

SERVICE DATA

SS062-22

Brake pedal height (from asphalt sheet)		154.0 - 164.0 mm (6.063 - 6.457 in.)
Brake pedal freeplay		1.0 - 6.0 mm (0.04 - 0.24 in.)
Stop light switch clearance		1.5 - 2.5 mm (0.059 - 0.098 in.)
Brake pedal reserve distance at 490 N (50 kgf, 110.2 lbf)		More than 99 mm (3.90 in.)
Brake booster push rod to piston clearance (w/ SST)		0 mm (0 in.)
Front brake pad thickness	STD	11.0 mm (0.433 in.)
Front brake pad thickness	Minimum	1.0 mm (0.039 in.)
Front brake disc thickness	STD	32.0 mm (1.260 in.)
Front brake disc thickness	Minimum	30.0 mm (1.181 in.)
Front brake disc runout	Maximum	0.05 mm (0.0020 in.)
Rear brake pad thickness	STD	10.5 mm (0.413 in.)
Rear brake pad thickness	Minimum	1.0 mm (0.039 in.)
Rear brake disc thickness	STD	12.0 mm (0.472 in.)
Rear brake disc thickness	Minimum	10.5 mm (0.413 in.)
Rear brake disc runout	Maximum	0.05 mm (0.0020 in.)
Rear brake disc inside diameter	STD	190 mm (7.48 in.)
Rear brake disc inside diameter	Maximum	191 mm (7.52 in.)
Parking brake shoe lining thickness for rear disc brake	STD	2.5 mm (0.098 in.)
Parking brake shoe lining thickness for rear disc brake	Minimum	1.0 mm (0.039 in.)
Parking brake pedal lever at 196 N (20 kgf, 44.1 lbf)		5 - 8 clicks
Parking brake clearance between rear shoe and lever		Less than 0.35 mm (0.0138 in.)
Parking brake adjusting shim thickness for rear disc brake		0.3 mm (0.012 in.) 0.6 mm (0.024 in.) 0.9 mm (0.035 in.)