

MAJOR TECHNICAL SPECIFICATIONS

Area			Europe	
Body Type			Sedan	
Model Code			USE20L-FEZRHW	USE20R-FEZRHW
Major Dimensions & Vehicle Weights				
Overall	Length	mm (in.)	4660 (183.4)	4660 (183.4)
	Width	mm (in.)	1815 (71.4)	1815 (71.4)
	Height	mm (in.)	1415 (55.7)	1415 (55.7)
Wheel Base		mm (in.)	2730 (107.4)	2730 (107.4)
Tread	Front	mm (in.)	1560 (61.4)	1560 (61.4)
	Rear	mm (in.)	1515 (59.6)	1515 (59.6)
Room	Length	mm (in.)	1855 (73.0)	1855 (73.0)
	Width	mm (in.)	1475 (58.1)	1475 (58.1)
	Height	mm (in.)	1165 (45.9), 1120 (44.1)*	1165 (45.9), 1120 (44.1)*
Overhang	Front	mm (in.)	885 (34.8)	885 (34.8)
	Rear	mm (in.)	1045 (41.1)	1045 (41.1)
Min. Running Ground Clearance		mm (in.)	120 (4.7)	120 (4.7)
Angle of Approach/Departure		degrees	12/14	12/14
Curb Weight	Front	kg (lb)	925 (2039)	925 (2039)
	Rear	kg (lb)	775 (1708)	775 (1708)
	Total	kg (lb)	1700 (3747)	1700 (3747)
Gross Vehicle Weight	Front	kg (lb)	1010 (2226)	1010 (2226)
	Rear	kg (lb)	1110 (2447)	1110 (2447)
	Total	kg (lb)	2120 (4673)	2120 (4673)
Luggage Compartment Capacity		m ³ (cu.ft.)	0.378 (13.3)	0.378 (13.3)
Fuel Tank Capacity		L (Us.gal, Imp.gal)	64 (16.9, 14.0)	64 (16.9, 14.0)
Performance				
Max. Speed		km/h (mph)	270 (170)	270 (170)
Max. Cruising Speed		km/h (mph)	230 (145)	230 (145)
Acceleration	0 to 100 km/h	sec.	4.8	4.8
	0 to 400 m	sec.	13.0	13.0
Max. Permissible Speed	1st Gear	km/h (mph)	61 (38)	61 (38)
	2nd Gear	km/h (mph)	103 (64)	103 (64)
	3rd Gear	km/h (mph)	150 (93)	150 (93)
	4th Gear	km/h (mph)	191 (119)	191 (119)
	5th Gear	km/h (mph)	228 (141)	228 (141)
	6th Gear	km/h (mph)	-	-
	7th Gear	km/h (mph)	-	-
	8th Gear	km/h (mph)	-	-
Min. Turning Radius	Tire	m (ft.)	5.1 (16.7)	5.1 (16.7)
	Body	m (ft.)	5.5 (18.0)	5.5 (18.0)
Engine				
Engine Type			2UR-GSE	2UR-GSE
No. of Cyls. & Arrangement			8-Cylinder, V Type	8-Cylinder, V Type
Valve Mechanism			32-valve, DOHC with Dual VVT-i	32-valve, DOHC with Dual VVT-i
Bore × Stroke		mm (in.)	94.0 × 89.5 (3.70 × 3.52)	94.0 × 89.5 (3.70 × 3.52)
Displacement		cm ³ (cu.in.)	4969 (303.2)	4969 (303.2)
Compression Ratio			11.8 : 1	11.8 : 1
Fuel System			EFI D-4S	EFI D-4S
Research Octane No. or Cetane No.			95 or higher	95 or higher
Max. Output (ECE)		kW@rpm	311@6600	311@6600
Max. Torque (ECE)		N·m@rpm	505@5200	505@5200
Engine Electrical				
Battery Capacity (5HR)		Voltage & Amp.hr.	12-55	12-55
Alternator Output		Watts	2160	2160
Starter Output		kW	2.0	2.0
Chassis				
Transmission Type			AA80E	AA80E
Gear Ratio	1st		4.596	4.596
	2nd		2.724	2.724
	3rd		1.863	1.863
	4th		1.464	1.464
	5th		1.231	1.231
	6th		1.000	1.000
	7th		0.824	0.824
	8th		0.685	0.685
	Reverse		2.176	2.176
Differential (Final) Gear Ratio			2.937	2.937
Brake Type	Front		Ventilated Disc	Ventilated Disc
	Rear		Ventilated Disc	Ventilated Disc
Suspension Type	Front		Double-wishbone	Double-wishbone
	Rear		Multi-link	Multi-link
Stabilizer Bar		Front/Rear	Standard/Standard	Standard/Standard
Steering Gear Type			Rack & Pinion	Rack & Pinion
Steering Gear Ratio			13.6	13.6
Power Steering Type			EPS	EPS

*: Models with Sliding Roof